

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 04/23/2015

Reviewed on 04/23/2015

*** 1 Identification**

- **Product identifier**
- **Trade name: Crawford's Vinyl Spackling Paste**
- **Product number:** CVSP
- **Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Crawford Products Co.
P.O. Box 4339
Whittier, CA 90607-4339
Phone: 323-721-6429
Fax: 323-721-0826
- **Emergency telephone number:** 323-721-6429

*** 2 Hazard(s) identification**

- **Classification of the substance or mixture**



GHS08 Health hazard

Muta. 1B H340 May cause genetic defects.
Carc. 1B H350 May cause cancer.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2A H319 Causes serious eye irritation.
Skin Sens. 1 H317 May cause an allergic skin reaction.
STOT SE 3 H335 May cause respiratory irritation.

- **Label elements**
- **GHS label elements**
The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS07



GHS08

- **Signal word** Danger
- **Hazard-determining components of labeling:**
Trade Secret
Trade Secret
Trade Secret
- **Hazard statements**
Causes skin irritation.
Causes serious eye irritation.
May cause an allergic skin reaction.

(Contd. on page 2)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 04/23/2015

Reviewed on 04/23/2015

Trade name: Crawford's Vinyl Spackling Paste

May cause genetic defects.

May cause cancer.

May cause respiratory irritation.

Precautionary statements

Avoid breathing dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area.

Wear protective gloves.

Wear eye protection / face protection.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Call a poison center/doctor if you feel unwell.

Wash contaminated clothing before reuse.

IF exposed or concerned: Get medical advice/attention.

If skin irritation or rash occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

If on skin: Wash with plenty of water.

Take off contaminated clothing and wash it before reuse.

Store locked up.

Store in a well-ventilated place. Keep container tightly closed.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Unknown acute toxicity:

69 percent of the mixture consists of ingredient(s) of unknown toxicity.

Classification system:**NFPA ratings (scale 0 - 4)**

Health = 1

Fire = 0

Reactivity = 0

HMS-ratings (scale 0 - 4)

HEALTH	1	Health = *1
FIRE	0	Fire = 0
REACTIVITY	0	Reactivity = 0

Hazard(s) not otherwise classified (HNOC): None known*** 3 Composition/information on ingredients**

Trade Secret

15-35%

Chemical characterization: Mixtures**Description:** Mixture of substances listed below with nonhazardous additions.**Dangerous Components:**

Trade Secret

69.4%

⚠ Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335

(Contd. on page 3)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 04/23/2015

Reviewed on 04/23/2015

Trade name: Crawford's Vinyl Spackling Paste

Trade Secret	11.5%
Trade Secret	0.5%
⚠ Asp. Tox. 1, H304; Flam. Liq. 4, H227	
Trade Secret	0.5%
⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410	
Trade Secret	0.5%
⚠ Flam. Liq. 3, H226; ⚠ Muta. 1B, H340; Carc. 1B, H350; Asp. Tox. 1, H304	
Trade Secret	0.5%
⚠ Eye Dam. 1, H318; ⚠ Aquatic Acute 1, H400; ⚠ Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317	

4 First-aid measures

- **Description of first aid measures**
- **After inhalation:** In case of unconsciousness, place patient securely on side position for transportation.
- **After skin contact:**
Immediately wash with water and soap and rinse thoroughly.
If skin irritation occurs, consult a doctor.
- **After eye contact:**
Rinse opened eye for at least 15 minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If swallowed and symptoms occur, consult a doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed:** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:**
As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent), and full protective gear to prevent contact with skin and eyes.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Not required.
- **Environmental precautions:**
Inform respective authorities in case of seepage into water course or sewage system.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (ie. sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
Dispose of the collected material according to regulations.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

(Contd. on page 4)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 04/23/2015

Reviewed on 04/23/2015

Trade name: Crawford's Vinyl Spackling Paste**7 Handling and storage**

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:** Keep protective respiratory device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters**

· Components with occupational exposure limits:	
Trade Secret	
NIOSH	Short-term value: 5 mg/m ³ Long-term value: 10 mg/m ³
NIOSH TWA	Short-term value: 5 mg/m ³ Long-term value: 10 mg/m ³ respirable dust
OSHA	Short-term value: 5 mg/m ³ Long-term value: 15 mg/m ³
OSHA TWA	Short-term value: 5 mg/m ³ Long-term value: 15 mg/m ³ respirable fraction
Trade Secret	
TLV	Long-term value: 5 mg/m ³

- **Additional information:** The lists that were valid during the creation of this SDS were used as basis.

- **Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

- The usual precautionary measures for handling chemicals should be followed.
- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing and wash before reuse.
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Avoid contact with the eyes and skin.
- **Breathing equipment:** Not required.

(Contd. on page 5)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 04/23/2015

Reviewed on 04/23/2015

Trade name: Crawford's Vinyl Spackling Paste**· Protection of hands:**

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Select glove material based on penetration times, rates of diffusion and degradation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.

· Eye protection:

Tightly sealed goggles

*** 9 Physical and chemical properties****· Information on basic physical and chemical properties****· General Information****· Appearance:**

Form:	Paste
Color:	Off white
Odor:	Odorless
Odor threshold:	Not determined.

· pH-value: Not applicable.

· Change in condition

Melting point/Melting range:	Not determined.
Boiling point/Boiling range:	72 °C (162 °F)

· Flash point: Not applicable.

· Flammability (solid, gaseous): Not determined.

· Ignition temperature: 427 °C (801 °F)

· Decomposition temperature: Not determined.

· Auto igniting: Product is not self-igniting.

· Danger of explosion: Product does not present an explosion hazard.

· Explosion limits:

Lower:	0.0 Vol %
Upper:	13.4 Vol %

· Vapor pressure @ 20 °C (68 °F): 111 hPa (83 mm Hg)

(Contd. on page 6)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 04/23/2015

Reviewed on 04/23/2015

Trade name: Crawford's Vinyl Spackling Paste

- **Density @ 20 °C (68 °F):** 2.198 g/cm³ (18.342 lbs/gal)
- **Relative density** Not determined.
- **Vapor density** Not applicable.
- **Evaporation rate** Not applicable.
- **Solubility in / Miscibility with Water:** Insoluble.
- **Partition coefficient (n-octanol/water):** Not determined.
- **Viscosity:**
 - Dynamic:** Not applicable.
 - Kinematic:** Not applicable.
- **Solvent content:**
 - Organic solvents:** 18.6 %
 - VOC content:** 18.6 %
- **Solids content:** 80.4 %
- **Other information** No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability** Stable under normal conditions.
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

***11 Toxicological information**

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

Trade Secret		
Oral	LD50	2920 mg/kg (rat)
Dermal	LD50	2335 mg/kg (rabbit)
Trade Secret		
Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>3000 mg/kg (rab)
Trade Secret		
	LC50/48 hrs	0.067 mg/l (Trout) 0.04 mg/l (daphnia)
Trade Secret		
Oral	LD50	>6800 mg/kg (rat)
Dermal	LD50	>3400 mg/kg (rab)
Inhalative	LC50/4 h	>10.2 mg/l (rat)
Trade Secret		
Oral	LD50	1020 mg/kg (rat)

(Contd. on page 7)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 04/23/2015

Reviewed on 04/23/2015

Trade name: Crawford's Vinyl Spackling Paste

Inhalative	LC50/4 h	0.8 mg/l (Trout) (96 hr)
<ul style="list-style-type: none"> · Primary irritant effect: · on the skin: Irritant to skin and mucous membranes. May cause an allergic skin reaction. · on the eye: Irritating effect. Causes serious eye irritation. · Sensitization: Sensitization possible through skin contact. · Additional toxicological information: The product shows the following dangers according to internally approved calculation methods for preparations: Irritant Carcinogenic. The product can cause inheritable damage. · Carcinogenic categories 		
· IARC (International Agency for Research on Cancer)		
Trade Secret		3
Trade Secret		3
Trade Secret		3
Trade Secret		2B
· NTP (National Toxicology Program)		
Trade Secret		R
· OSHA-Ca (Occupational Safety & Health Administration)		
None of the ingredients are listed.		

***12 Ecological information**

- **Toxicity**
- **Aquatic toxicity:**
Avoid release into the environment. Runoff from fire control or dilution water may cause pollution.

Trade Secret

EC50 4.4 mg/l (daphnia) (48 hr)

- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
Generally not hazardous for water
Harmful to aquatic organisms
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

(Contd. on page 8)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 04/23/2015

Reviewed on 04/23/2015

Trade name: Crawford's Vinyl Spackling Paste**13 Disposal considerations**

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**
- **DOT, ADR, ADN, IMDG, IATA** Non-Regulated Material
- **UN proper shipping name**
- **DOT, ADR, ADN, IMDG, IATA** Non-Regulated Material
- **Transport hazard class(es)**
- **DOT, ADR, ADN, IMDG, IATA**
- **Class** Non-Regulated Material
- **Packing group**
- **DOT, ADR, IMDG, IATA** Non-Regulated Material
- **Environmental hazards:** Not applicable.
- **Special precautions for user** Not applicable.
- **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.
- **UN "Model Regulation":** -

***15 Regulatory information**

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

· Section 355 (extremely hazardous substances):
None of the ingredients are listed.
· Section 313 (Specific toxic chemical listings):
Trade Secret
Trade Secret
Trade Secret
· TSCA (Toxic Substances Control Act):
Trade Secret
Trade Secret
Trade Secret
Trade Secret
Trade Secret
Trade Secret
Trade Secret
Trade Secret
Trade Secret
Trade Secret
Trade Secret
Trade Secret
Trade Secret

(Contd. on page 9)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 04/23/2015

Reviewed on 04/23/2015

Trade name: Crawford's Vinyl Spackling Paste· **California Proposition 65**· **Chemicals known to cause cancer:**

Trade Secret

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients are listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients are listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients are listed.

· **Carcinogenic categories**· **EPA (Environmental Protection Agency)**

Trade Secret

I

Trade Secret

D, CBD

· **TLV (Threshold Limit Value established by ACGIH)**

Trade Secret

A3

Trade Secret

A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients are listed.

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**

GHS07 GHS08

· **Signal word** Danger· **Hazard-determining components of labeling:**

Trade Secret

Trade Secret

Trade Secret

· **Hazard statements**

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

May cause genetic defects.

May cause cancer.

May cause respiratory irritation.

· **Precautionary statements**

Avoid breathing dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area.

Wear protective gloves.

Wear eye protection / face protection.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Obtain special instructions before use.

(Contd. on page 10)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 04/23/2015

Reviewed on 04/23/2015

Trade name: Crawford's Vinyl Spackling Paste

Do not handle until all safety precautions have been read and understood.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Call a poison center/doctor if you feel unwell.

Wash contaminated clothing before reuse.

IF exposed or concerned: Get medical advice/attention.

If skin irritation or rash occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

If on skin: Wash with plenty of water.

Take off contaminated clothing and wash it before reuse.

Store locked up.

Store in a well-ventilated place. Keep container tightly closed.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **National regulations:**

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

· **State Right to Know**

Trade Secret	⚠ Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	60-90%
Trade Secret		15-35%
Trade Secret		15-35%
Trade Secret	⚠ Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	≤ 2.5%
Trade Secret	⚠ Skin Irrit. 2, H315; Eye Irrit. 2B, H320	≤ 2.5%
Trade Secret	⚠ Asp. Tox. 1, H304; Flam. Liq. 4, H227	≤ 2.5%
56-81-5 Glycerol		0.15%

· **Information about limitation of use:**

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

· **Date of preparation / last revision** 04/23/2015 / 7

· **Abbreviations and acronyms:**

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Liq. 3: Flammable liquids, Hazard Category 3

Flam. Liq. 4: Flammable liquids, Hazard Category 4

Acute Tox. 4: Acute toxicity, Hazard Category 4

(Contd. on page 11)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 04/23/2015

Reviewed on 04/23/2015

Trade name: Crawford's Vinyl Spackling Paste

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1
Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A
Skin Sens. 1: Sensitisation - Skin, Hazard Category 1
Muta. 1B: Germ cell mutagenicity, Hazard Category 1B
Carc. 1B: Carcinogenicity, Hazard Category 1B
STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3
Asp. Tox. 1: Aspiration hazard, Hazard Category 1
Aquatic Acute 1: Hazardous to the aquatic environment - AcuteHazard, Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - Chronic Hazard, Category 1

· *** Data compared to the previous version altered.**

SDS created by MSDS Authoring Services www.msdsauthoring.com (877) 204-9106